



POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 28/04/2011 Revision date: 24/03/2025 Supersedes version of: 11/03/2022 Version: 11.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : POLA-G Cement
UFI : C5JT-H5EY-XRS0-5SVR
Product code : 330593

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Use of the substance/mixture : Adhesives, binding agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Gebr. FALLER GmbH GmbH
Kreuzstraße 9
DE 78148 Gütenbach
Germany
T +49-7723-651-0, F +49-7723-651-161
kundendienst@faller.de

1.4. Emergency telephone number

Emergency number : +49-7723-651-0 (8:30 – 16:30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Acute toxicity (oral), Category 4 H302
Skin corrosion/irritation, Category 2 H315
Specific target organ toxicity – Single exposure, Category 2 H371
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause damage to organs. May cause drowsiness or dizziness. Harmful if swallowed. Causes skin irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| | |
|--------------------------------|--|
| Signal word (CLP) | : Danger |
| Contains | : propan-2-ol; isopropyl alcohol; isopropanol; Methylal; Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction With hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (– 4°F to 374°F).] |
| Hazard statements (CLP) | : H225 - Highly flammable liquid and vapour. H302 - Harmful if swallowed. H315 - Causes skin irritation. H336 - May cause drowsiness or dizziness. H371 - May cause damage to organs. H411 - Toxic to aquatic life with long lasting effects. |
| Precautionary statements (CLP) | : P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P391 - Collect spillage. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. |
| Child-resistant fastening | : Not applicable |
| Tactile warning | : Applicable |

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|--|---------|--|
| Methylal substance with national workplace exposure limit(s) (IE) | CAS-No.: 109-87-5 EC-No.: 203-714-2 | 25 – 50 | Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT SE 2, H371 |
| Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction With hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (– 4°F to 374°F).] (Note P) | CAS-No.: 64742-49-0 EC-No.: 265-151-9 EC Index-No.: 649-328-00-1 | 10 – 25 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|---|-----------|---|
| propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (IE) | CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25 | 0.5 – 2.5 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |

Note P: Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse eyes with water as a precaution. |
| First-aid measures after ingestion | : Rinse mouth. Call a poison center or a doctor if you feel unwell. |
| First-aid measures for first aider | : First aid workers will be equipped with suitable personal protective equipment. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|--------------------------------------|
| Symptoms/effects | : May cause drowsiness or dizziness. |
| Symptoms/effects after inhalation | : None under normal conditions. |
| Symptoms/effects after skin contact | : Irritation. |
| Symptoms/effects after eye contact | : None under normal conditions. |
| Symptoms/effects after ingestion | : Harmful if swallowed. |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Special hazards arising from the substance or mixture

| | |
|--|---------------------------------------|
| Fire hazard | : Highly flammable liquid and vapour. |
| Explosion hazard | : No direct explosion hazard. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

5.3. Advice for firefighters

| | |
|--------------------------------|---|
| Firefighting instructions | : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials : Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| | |
|---|--|
| propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) | |
| Ireland - Occupational Exposure Limits | |
| Local name | Isopropyl alcohol [Propan-2-ol] |
| OEL TWA | 200 ppm |
| OEL STEL | 400 ppm |
| Remark | Advisory OELV (Advisory Occupational Exposure Limit Values), Skin (Substances which have the capacity to penetrate intact skin when they come in contact with it and be absorbed into the body. A substantial contribution to the total body burden via dermal exposure is possible) |
| Regulatory reference | Chemical Agents Code of Practice 2024 |
| Ireland - Biological limit values | |
| Local name | 2-Propanol |
| BMGV | 40 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B (Background), Ns (Non-specific) |
| Regulatory reference | Biological Monitoring Guidelines (HSA, 2011) |
| Methylal (109-87-5) | |
| Ireland - Occupational Exposure Limits | |
| Local name | Methylal [Dimethoxymethane] |
| OEL TWA | 3100 mg/m³ |
| | 1000 ppm |
| Remark | Advisory OELV (Advisory Occupational Exposure Limit Values) |
| Regulatory reference | Chemical Agents Code of Practice 2024 |

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | : Liquid |
| Colour | : Colourless. |
| Appearance | : Viscous. |
| Odour | : ester-like. |
| Odour threshold | : Not available |
| Melting point | : Not applicable |
| Freezing point | : Not available |
| Boiling point | : > 35 °C |
| Flammability | : Highly flammable liquid and vapour. |
| Lower explosion limit | : Not available |
| Upper explosion limit | : Not available |
| Flash point | : < 23 °C |
| Auto-ignition temperature | : Not available |
| Decomposition temperature | : Not available |
| pH | : Not available |
| Viscosity, kinematic | : Not available |
| Solubility | : Material nearly insoluble in water. Soluble in hydrocarbons. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Vapour pressure | : Not available |
| Vapour pressure at 50°C | : Not available |
| Density | : Not available |
| Relative density | : Not available |
| Relative vapour density at 20°C | : Not available |
| Particle characteristics | : Not applicable |

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

| POLA-G Cement | |
|---|---|
| ATE CLP (oral) | 1000 mg/kg bodyweight |
| propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) | |
| LD50 oral rat | 5840 mg/kg Source: ECHA |
| LD50 oral | 4396 mg/kg bodyweight |
| LD50 dermal rabbit | 12800 mg/kg Source: ECHA |
| LD50 dermal | 12800 mg/kg bodyweight |
| LC50 Inhalation - Rat (Dust/Mist) | 46600 mg/l |
| Methylal (109-87-5) | |
| LD50 oral rat | 6423 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method) |
| LD50 dermal rabbit | > 5000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction With hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (– 4°F to 374°F).] (64742-49-0)

| | |
|-----------------------|--|
| LD50 dermal rat | 2800 – 3100 mg/kg bodyweight Animal: rat |
| LC50 Inhalation - Rat | > 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity) |

| | |
|-----------------------------------|---------------------------|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

| | |
|------------|----------------------|
| IARC group | 3 - Not classifiable |
|------------|----------------------|

| | |
|-----------------------|--|
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : May cause damage to organs. May cause drowsiness or dizziness. |

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

Methylal (109-87-5)

| | |
|----------------------|-----------------------------|
| STOT-single exposure | May cause damage to organs. |
|----------------------|-----------------------------|

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction With hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (– 4°F to 374°F).] (64742-49-0)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

| | |
|------------------------|------------------|
| STOT-repeated exposure | : Not classified |
|------------------------|------------------|

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction With hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (– 4°F to 374°F).] (64742-49-0)

| | |
|--|---|
| LOAEC (inhalation, rat, vapour, 90 days) | 4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study) |
| NOAEC (inhalation, rat, vapour, 90 days) | 2355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study) |

| | |
|-------------------|------------------|
| Aspiration hazard | : Not classified |
|-------------------|------------------|

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction With hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (– 4°F to 374°F).] (64742-49-0)

| | |
|----------------------|------------|
| Viscosity, kinematic | 20.5 mm²/s |
|----------------------|------------|

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

No additional information available

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|--|
| Ecology - general | : Toxic to aquatic life with long lasting effects. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified |
| Hazardous to the aquatic environment, long-term (chronic) | : Toxic to aquatic life with long lasting effects. |

| propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) | |
|---|--|
| LC50 - Fish [1] | 10000 mg/l Test organisms (species): Pimephales promelas |
| LC50 - Fish [2] | 9640 mg/l Test organisms (species): Pimephales promelas |
| EC50 - Other aquatic organisms [1] | 13299 mg/l waterflea |
| EC50 - Other aquatic organisms [2] | > 1000 mg/l |

| Methylal (109-87-5) | |
|----------------------|---|
| LC50 - Fish [1] | > 1000 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) |
| EC50 - Crustacea [1] | > 1200 mg/l Test organisms (species): Daphnia magna |
| EC50 72h - Algae [1] | 9120 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| EC50 96h - Algae [1] | 874.12 mg/l Test organisms (species): other: |
| NOEC (chronic) | 150.5 mg/l Test organisms (species): Daphnia magna Duration: '30 d' |
| NOEC chronic fish | 450281 mg/l Test organisms (species): other: Duration: '30 d' |

| Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction With hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (– 4°F to 374°F).] (64742-49-0) | |
|---|--|
| EC50 72h - Algae [1] | 32 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| EC50 72h - Algae [2] | 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| LOEC (chronic) | 0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | 0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |

12.2. Persistence and degradability

| POLA-G Cement | |
|-------------------------------|--------------------|
| Persistence and degradability | Rapidly degradable |

12.3. Bioaccumulative potential

| propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) | |
|---|------|
| Partition coefficient n-octanol/water (Log Pow) | 0.05 |

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--|---|
| Regional waste regulation | : Disposal must be done according to official regulations. |
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector’s sorting instructions. |
| Sewage disposal recommendations | : Disposal must be done according to official regulations. |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations. |
| Additional information | : Flammable vapours may accumulate in the container. Do not re-use empty containers. |

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

| ADR | IMDG | IATA | ADN | RID |
|--|---|---|---|---|
| 14.1. UN number or ID number | | | | |
| UN 1133 | UN 1133 | UN 1133 | UN 1133 | UN 1133 |
| 14.2. UN proper shipping name | | | | |
| ADHESIVES | ADHESIVES | Adhesives | ADHESIVES | ADHESIVES |
| Transport document description | | | | |
| UN 1133 ADHESIVES, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS | UN 1133 ADHESIVES, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS | UN 1133 Adhesives, 3, II, ENVIRONMENTALLY HAZARDOUS | UN 1133 ADHESIVES, 3, II, ENVIRONMENTALLY HAZARDOUS | UN 1133 ADHESIVES, 3, II, ENVIRONMENTALLY HAZARDOUS |
| 14.3. Transport hazard class(es) | | | | |
| 3 | 3 | 3 | 3 | 3 |
| | | | | |
| 14.4. Packing group | | | | |
| II | II | II | II | II |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment: Yes | Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-E EmS-No. (Spillage): S-D | Dangerous for the environment: Yes | Dangerous for the environment: Yes | Dangerous for the environment: Yes |
| No supplementary information available | | | | |

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| | |
|---|---------------------|
| Special provisions (ADR) | : 640D |
| Limited quantities (ADR) | : 5L |
| Excepted quantities (ADR) | : E2 |
| Packing instructions (ADR) | : P001, IBC02, R001 |
| Special packing provisions (ADR) | : PP1 |
| Mixed packing provisions (ADR) | : MP19 |
| Portable tank and bulk container instructions (ADR) | : T4 |
| Portable tank and bulk container special provisions (ADR) | : TP1, TP8 |
| Tank code (ADR) | : LGBF |
| Vehicle for tank carriage | : FL |
| Transport category (ADR) | : 2 |
| Special provisions for carriage - Operation (ADR) | : S2, S20 |
| Hazard identification number (Kemler No.) | : 33 |
| Orange plates | : |



| | |
|-------------------------------|-------|
| Tunnel restriction code (ADR) | : D/E |
|-------------------------------|-------|

Transport by sea

| | |
|------------------------------------|---|
| Limited quantities (IMDG) | : 5 L |
| Excepted quantities (IMDG) | : E2 |
| Packing instructions (IMDG) | : P001 |
| Special packing provisions (IMDG) | : PP1 |
| IBC packing instructions (IMDG) | : IBC02 |
| Tank instructions (IMDG) | : T4 |
| Tank special provisions (IMDG) | : TP1, TP8 |
| Stowage category (IMDG) | : B |
| Properties and observations (IMDG) | : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition. |

Air transport

| | |
|--|--------|
| PCA Excepted quantities (IATA) | : E2 |
| PCA Limited quantities (IATA) | : Y341 |
| PCA limited quantity max net quantity (IATA) | : 1L |
| PCA packing instructions (IATA) | : 353 |
| PCA max net quantity (IATA) | : 5L |
| CAO packing instructions (IATA) | : 364 |
| CAO max net quantity (IATA) | : 60L |
| Special provisions (IATA) | : A3 |
| ERG code (IATA) | : 3L |

Inland waterway transport

| | |
|-----------------------------------|-------------|
| Classification code (ADN) | : F1 |
| Special provisions (ADN) | : 640D |
| Limited quantities (ADN) | : 5 L |
| Excepted quantities (ADN) | : E2 |
| Equipment required (ADN) | : PP, EX, A |
| Ventilation (ADN) | : VE01 |
| Number of blue cones/lights (ADN) | : 1 |

Rail transport

| | |
|---------------------------|--------|
| Classification code (RID) | : F1 |
| Special provisions (RID) | : 640D |
| Limited quantities (RID) | : 5L |

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| | |
|---|---------------------|
| Excepted quantities (RID) | : E2 |
| Packing instructions (RID) | : P001, IBC02, R001 |
| Special packing provisions (RID) | : PP1 |
| Mixed packing provisions (RID) | : MP19 |
| Portable tank and bulk container instructions (RID) | : T4 |
| Portable tank and bulk container special provisions (RID) | : TP1, TP8 |
| Tank codes for RID tanks (RID) | : LGBF |
| Transport category (RID) | : 2 |
| Colis express (express parcels) (RID) | : CE7 |
| Hazard identification number (RID) | : 33 |

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

| | |
|-------|---|
| ACGIH | American Conference of Government Industrial Hygienists |
|-------|---|

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Abbreviations and acronyms: | |
|-----------------------------|---|
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| BLV | Biological limit value |
| BOD | Biochemical oxygen demand (BOD) |
| CAS-No. | Chemical Abstract Service number |
| CLP | Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 |
| COD | Chemical oxygen demand (COD) |
| CSA | Chemical safety assessment |
| DMEL | Derived Minimal Effect level |
| DNEL | Derived-No Effect Level |
| EC-No. | European Community number |
| EC50 | Median effective concentration |
| ED | Endocrine disruptor |
| EN | European Standard |
| EWC | European waste catalogue |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Median lethal concentration |
| LD50 | Median lethal dose |
| LOAEL | Lowest Observed Adverse Effect Level |
| Log Kow | Partition coefficient n-octanol/water (Log Kow) |
| Log Pow | Partition coefficient n-octanol/water (Log Pow) |
| MAK | maximum workplace concentration |
| NOAEC | No-Observed Adverse Effect Concentration |
| NOAEL | No-Observed Adverse Effect Level |
| NOEC | No-Observed Effect Concentration |
| N.O.S. | Not Otherwise Specified |
| OECD | Organisation for Economic Co-operation and Development |
| OEL | Occupational Exposure Limit |
| OSHA | Occupational Safety & Health Administration |
| PBT | Persistent Bioaccumulative Toxic |
| PNEC | Predicted No-Effect Concentration |

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

| | |
|------|--|
| PPE | Personal protection equipment |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| SDS | Safety Data Sheet |
| STP | Sewage treatment plant |
| TF | Technical function |
| ThOD | Theoretical oxygen demand (ThOD) |
| TLM | Median Tolerance Limit |
| TWA | Time Weighted Average |
| VOC | Volatile Organic Compounds |
| vPvB | Very Persistent and Very Bioaccumulative |
| UFI | Unique Formula Identifier |

Full text of H- and EUH-statements:

| | |
|---------------------|--|
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment – Chronic Hazard, Category 2 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT SE 2 | Specific target organ toxicity – Single exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis |
| H225 | Highly flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H371 | May cause damage to organs. |
| H411 | Toxic to aquatic life with long lasting effects. |

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.