



POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 28/04/2011 Revision date: 11/03/2022 Supersedes version of: 16/12/2020 Version: 10.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : POLA-G Cement
UFI : WFPF-68WR-9236-KVR4
Product code : 330593

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Use of the substance/mixture : Adhesives, binding agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Gebr. FALLER GmbH
Kreuzstraße 9
78148 Gütenbach - Germany
T +49-7723-651-0 - F +49-7723-651-161
kundendienst@faller.de

1.4. Emergency telephone number

Emergency number : +49-7723-651-0 (8:30 – 16:30)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Acute toxicity (oral), Category 4 H302
Skin corrosion/irritation, Category 2 H315
Specific target organ toxicity – Single exposure, Category 2 H371
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause damage to organs. May cause drowsiness or dizziness. Harmful if swallowed. Causes skin irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Signal word (CLP)	: Danger
Contains	: propan-2-ol; isopropyl alcohol; isopropanol, Methylal, Naphtha (petroleum), hydrotreated light
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H302 - Harmful if swallowed. H315 - Causes skin irritation. H336 - May cause drowsiness or dizziness. H371 - May cause damage to organs. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Child-resistant fastening	: Not applicable
Tactile warning	: Applicable

2.3. Other hazards

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Methylal substance with national workplace exposure limit(s) (GB)	(CAS-No.) 109-87-5 (EC-No.) 203-714-2	25 – 50	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 STOT SE 2, H371
Naphtha (petroleum), hydrotreated light (Note P)	(CAS-No.) 64742-49-0 (EC-No.) 265-151-9 (EC Index-No.) 649-328-00-1	10 – 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (GB)	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0 (REACH-no) 01-2119457558-25	0.5 – 2.5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Note P: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einacs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

Full text of H- and EUH-statements: see section 16

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA) [1]	999 mg/m ³
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Methylal (109-87-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Dimethoxymethane
WEL TWA (OEL TWA) [1]	3160 mg/m ³
WEL TWA (OEL TWA) [2]	1000 ppm
WEL STEL (OEL STEL)	3950 mg/m ³
WEL STEL (OEL STEL) [ppm]	1250 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: Viscous.
Odour	: ester-like.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: > 35 °C
Flammability	: Not applicable
Explosive limits	: Not available

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 23 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Material nearly insoluble in water. Soluble in hydrocarbons.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

POLA-G Cement

ATE CLP (oral)	1000 mg/kg bodyweight
----------------	-----------------------

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	4396 mg/kg bodyweight
LD50 dermal	12800 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	46600 mg/l

Methylal (109-87-5)	
LD50 oral rat	6423 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause damage to organs. May cause drowsiness or dizziness.

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

Methylal (109-87-5)	
STOT-single exposure	May cause damage to organs.

Naphtha (petroleum), hydrotreated light (64742-49-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LC50 - Fish [1]	9640 mg/l
EC50 - Other aquatic organisms [1]	13299 mg/l waterflea

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EC50 - Other aquatic organisms [2]	> 1000 mg/l
------------------------------------	-------------

Methylal (109-87-5)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 1200 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	9120 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	874.12 mg/l Test organisms (species): other:
NOEC (chronic)	150.5 mg/l Test organisms (species): Daphnia magna Duration: '30 d'
NOEC chronic fish	450281 mg/l Test organisms (species): other: Duration: '30 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1133	UN 1133	UN 1133
14.2. UN proper shipping name		
ADHESIVES	ADHESIVES	Adhesives
Transport document description		
UN 1133 ADHESIVES, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1133 ADHESIVES, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1133 Adhesives, 3, II, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)		
3	3	3

POLA-G Cement

Safety Data Sheet


according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 640D
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP8
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Transport by sea

Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ERG code (IATA) : 3L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

POLA-G Cement

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12
SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.